

DVP 505A Digital Visual Presenter

- High Resolution Color Camera
- XGA Computer Output
- Auto Focus, 12X Zoom
- 32 Picture Memory
- Optical and Digital Zoom
- Dual Lamps & Back Light
- Wireless Remote Control
- S-Video & Composite Video Outputs
- Microphone, Audio, and DC12V Power Outlets

Features

The DVP505A consists of a high-resolution color camera on a moveable extendable arm positioned over a large stage, which has a backlight. Sidelights on arms provide additional illumination for the top and side of objects or documents. The camera provides images that can be shown using a multimedia projector, viewed with a monitor or plasma panel, or captured with a computer. The camera has a resolution of 1024 x 768 pixels, XGA and provides outputs in XGA or SVGA computer signal format plus composite and S-video. With electronically controlled 12x optical and 4x digital zoom, plus auto focus, the details of an object can quickly be viewed.

Your presentation will be enhanced by the array of features such as a 32 image memory, image freeze, microphone input, remote control, electronic pointer, and a electronic switch for a computer signal pass through. Control is easy with panel push buttons or using the credit card size remote control. This presenter is perfect for viewing objects, evidence, papers, X-rays, or demonstrations.





DVP 505A Digital Visual Presenter

The DVP 505A is a digital presenter consisting of a high-resolution color camera on a moveable extendable arm mounted over a stage with a backlight. There are also lights on arms located on each side of the stage for illumination of the subject. This presenter is very easy to use and can be controlled by the built-in controls or via credit card size remote control that is stored in the presenter's base. It merely requires plugging into standard power, connection of the computer or video cable to the projector or display monitor, and the push of the power button. After that the user can position the camera arm and push the auto focus button. The DVP 505A has a 12X optical and 4X digital zoom range controlled by buttons. The camera which has auto focus can easily view objects at up to 80X magnification. Up to 32 images can be captured by merely pushing the "Capture" button on the remote.

Objects such as transparencies can be illuminated from the backside using the stage lamp or illuminated from above by the side fluorescent lamps. The presenter is the perfect tool for providing images of objects, evidence, papers, X-rays, or demonstrations in the classroom, conference room, courtroom, at the podium, or for video conferencing.

Key features:

- High Resolution Color Camera
- XGA Computer Output
- Auto Focus, 12X Zoom
- 32 Picture Memory
- Optical and Digital Zoom
- Dual Lamps & Back Light
- Wireless Remote Control
- S-Video & Composite Video Outputs
- Microphone, Audio, and DC12V Power Outlets



Dukane Corporation Audio Visual Products Division 2900 Dukane Drive St. Charles, Illinois 60174 Toll-free: 800-676-2485 Fax: 630-584-5156 avsales@dukcorp.com www.dukcorp.com/av



Specifications

Lens Shooting Area Range

Focal Distance

Zoom Control

Focusing Iris Side Illumination Back light, stage

Image pickup Total pixels effective Synchronization Frame Rate White Balance Exposure Freeze Image Modes Image Signal Level Output Signals

RGB, Computer DVI S-Video Composite Video Audio USB DC 12V Mouse Port RS-232C Mic Input Two Programmable Presets Menu Image Memory Freeze Gamma Accessories Included **DVP 505A** F2.9 to F3.5, FL=5.9mm to 59mm 14.2" x 10.6" to 1.6"x 1.2"

(Transparency 8" x 11")) 0 to 19" above the stage surface and to inifinity pointing the camera outward. Motorized 12x optical and 4x digital 6.7x mechanical, total 80x Automatic/Manual Auto/Fine tune 2 lamps (1 per side) fluorescent on arm. Size, 10.6" x 8.2" fluorescent, cold cathode 1/3" CCD progressive scan 1077 (H) x 778 (V), XGA (H) 60k/47kHz, (V) 75Hz 20 Frame/sec Auto/Manual Auto/Manual Push button operation Photo/Text/Inverse/Grayscale 0.7 Vpp RGB analog, XGA 75Hz, SVGA 75Hz, S-Video, NTSC/PAL, Composite, NTSC/PAL D-sub, 15 pin (VGA) **Digital & Analog Connector** Mini Din 4 pin RCA jack Stereo mini jack Standard socket, Type B DC jack, 500mA Standard PS/2, Menu and pointer D-sub 9 pin male Stereo mini jack Yes On Screen 32 Images

Safety Weight Shipping Weight Power Requirements Dimensions cable, user manual CD, DVI cable, PS2 mouse, 4 slide holder, negative film holder, DVI/VGA adapter, computer cable (VGA), USB cable, and soft carry case. UL/C-UL, FCC Class A 9.7 lbs. 20 lbs. AC100-240VAC, 50/60Hz Folded, 20" L x 13.8" W x 4" H Open, 25.2" L x 13.8" W x 25" H

Wireless full function remote control, power

Photo/Text/Grey/Film Modes

Five (5) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply).Includes Dukane's FREE 1 year *Peace-of-Mind Loaner Program*.

Yes

